POWERSCREEN®
TRAKPACTOR 480
HORIZONTAL IMPACTOR

GET STARTED



TECHNICAL SPECIFICATION - REV 0 01/10/2022

To use my interactive features I need to be opened in 'Adobe Acrobat Reader' click here to download



TRAKPACTOR 480

- OVERVIEW
  - FEATURES & BENEFITS
- CRUSHER
  - CRUSHER SPECIFICATION
  - CRUSHER FEATURES
- HOPPER
- VIBRATING GRIZZLY FEEDER
- PRODUCT CONVEYOR
- POWER UNIT & HYDRAULICS
- TRACKS
- PLANT CONTROLS & OTHER
- OPTIONS
  - OPTIONS 1
- POWERSCREEN® PULSE
- DIMENSIONS

OVERVIEW

SPECIFICATION

Total Weight:	47,650kg (105,050lbs) bypass conveyor & hopper extensions	
Transport	**Length**	16.38m (53' 9")
	Height	3.6m (11' 10")
	Width	2.78m (9' 2")
Working	**Length**	15.89m (52' 2'')
	Height	4.25m (13' 11")
	Width	5.43m (17' 10")
Crusher Type:	Twin apron 4 bar impact crusher, feed opening 1270mm x 870mm (50" x 34")	
Power Unit	Tier 2 Scania DC9 294kW (400hp), Tier 4F Scania DC9 294kW (400hp) or Stage V Scania DC9 294kW (400hp)	
Plant Colour	RAL 5021, RAL 7024, RAL 9005	



APPLICATIONS

Aggregate
Blasted rock
River rock

Recycling
C&D waste
Foundry waste

Mining
Processed ores
Processed minerals



TRAKPACTOR 480

- OVERVIEW
  - FEATURES & BENEFITS
- CRUSHER
  - CRUSHER SPECIFICATION
  - CRUSHER FEATURES
- HOPPER
- VIBRATING GRIZZLY FEEDER
- PRODUCT CONVEYOR
- POWER UNIT & HYDRAULICS
- TRACKS
- PLANT CONTROLS & OTHER
- OPTIONS
  - OPTIONS 1
- POWERSCREEN® PULSE
- DIMENSIONS

FEATURES & BENEFITS

The Powerscreen® Trakpactor 480 horizontal shaft impactor is designed for processing soft to medium-hard primary & secondary materials such as natural rock & construction derived materials like asphalt, recycling & demolition waste. Material is fed into the large feed hopper, with a vibrating grizzly feeder which features a selectable crusher bypass facility & optional fines discharge conveyor. Load sensing ensures the wide crusher inlet opening receives a continuous feed of pre-screened material, avoiding unnecessary crusher wear.

The Powerscreen® Trakpactor 480's robust impact chamber features a twin apron, 4 bar rotor design, with hydraulic release aprons, hydraulic setting adjustment, hydraulic crusher overload & is driven directly off the engine via clutch for optimum fuel economy. Next, crushed material passes directly onto the full length product conveyor. The product conveyor features a raise/lower facility to aid clearance of rebar in the event of a blockage. The plant has been designed with ease of maintenance in mind. Hydraulic banks, battery access and control valves are at eye level to make setup and operation much easier.


- Output potential of up to 480 tph / 529 US tph - depending on material type & crusher settings
- Suitable for a variety of feed materials, ideal for recycling, demolition & quarry applications
- Double deck grizzly feeder with under screen
- Load management system to control feeder speed
- Proven impact crusher with hydraulic overload protection, 4 bar rotor & twin apron design
- Heavy duty under crusher impact bars as standard
- Bypass conveyor selection on either side of plant (optional)
- Chamber drive via clutch & highly fuel efficient direct drive system
- Crusher speed variation through user friendly PLC control system
- Hydraulic raise/lower product conveyor
- Radio remote control as standard
- Powerscreen Pulse telemetry as standard



TRAKPACTOR 480

- OVERVIEW
  - FEATURES & BENEFITS
- CRUSHER
  - CRUSHER SPECIFICATION
  - CRUSHER FEATURES
- HOPPER
- VIBRATING GRIZZLY FEEDER
- PRODUCT CONVEYOR
- POWER UNIT & HYDRAULICS
- TRACKS
- PLANT CONTROLS & OTHER
- OPTIONS
  - OPTIONS 1
- POWERSCREEN® PULSE
- DIMENSIONS

CRUSHER



PRINCIPAL COMPONENTS

1: Control Cylinder
2: Top Impact Apron
3: Apron Adjustment Spindle
4: Control Cylinder
5: Bottom Impact Apron
6: Rotor
7: Full Blow Bar
8: Inlet Wear Beam
9: Inlet Plate
10: Wear Liners
11: Crusher Inlet lid

PRINCIPLES OF OPERATION

Material enters via crusher opening & slides down the inlet chute where it is struck by the blow bars fixed within the rotor. This initial impact breaks the material which is then accelerated towards the top apron where more reduction takes place on impact. This material then falls back onto the blow bars & the cycle is repeated until the material is small enough to pass between the top apron & blow bar. Further reduction occurs on the bottom apron until the material can again pass through the gap & discharge from the underside of the crusher.

Should an un-crushable object enter the chamber, the overload cylinders will relieve & allow the object to pass. The cylinders will then return to the pre-set crushing position. The pre-set gap is adjusted by turning the adjustment spindle whilst the weight of the apron is held on the cylinder (hydraulic assist).

The hydraulic cylinders are pre-loaded to minimise apron bounce & wear on the cylinders.
This arrangement also greatly reduces the oversize produced & is Patented: GB2455203




TRAKPACTOR 480

- OVERVIEW
  - FEATURES & BENEFITS
- CRUSHER
  - CRUSHER SPECIFICATION
  - CRUSHER FEATURES
- HOPPER
- VIBRATING GRIZZLY FEEDER
- PRODUCT CONVEYOR
- POWER UNIT & HYDRAULICS
- TRACKS
- PLANT CONTROLS & OTHER
- OPTIONS
  - OPTIONS 1
- POWERSCREEN® PULSE
- DIMENSIONS

CRUSHER SPECIFICATION

Feed opening:	1270mm x 870mm (50" x 34")
Max lump size*:	450-500mm³ (18-20in³) / 800 x 800 x 250mm (31 x 31 x 10'') *depending on material & blow bar specification
Rotor width:	1245mm (49")
Rotor diameter:	1065mm (42")
Number of aprons:	2
Max clearance:	Top apron: 180mm (7") Bottom apron: 190mm (7.5'')
Max OSS setting:	150mm (6") upper apron, 75mm (3 ") lower apron
Min CSS setting:	50mm (2 ") upper apron, 18mm (0.7 ") lower apron
Blow bars:	Total of 4 blow bars
Blow bar removal:	Vertically
Blow bar configuration:	2 full & 2 half (optional 4 full)
Setting adjustment:	Hydraulic assist
Overload protection:	Hydraulic
Rotor speeds:	535 - 845rpm (30 - 40m/s) (98 - 131ft/s)
Applications:	Demolition / recycling / quarry
Crusher weight:	11,000kg (24,251lbs)
Full blow bar weight:	310kg (383lbs)
Side liners:	20mm (thick, abrasive resistant steel)



PRINCIPAL COMPONENTS

1: Inlet lid
2: Main welded body
3: Impactor hinged section
4: Inspection covers
5: Hydraulic overload & adjustment cylinders
6: Toggle bolts
7: Inspection covers
8: Trunions
9: Hinged section opening cylinder



TRAKPACTOR 480

- OVERVIEW
  - FEATURES & BENEFITS
- CRUSHER
  - CRUSHER SPECIFICATION
  - CRUSHER FEATURES
- HOPPER
- VIBRATING GRIZZLY FEEDER
- PRODUCT CONVEYOR
- POWER UNIT & HYDRAULICS
- TRACKS
- PLANT CONTROLS & OTHER
- OPTIONS
  - OPTIONS 1
- POWERSCREEN® PULSE
- DIMENSIONS

CRUSHER FEATURES

Crusher body: Fabricated from steel plate & fully lined with replaceable abrasion resistant liner plates. Hinged side door allows access to apron tips & rotor for gap measurements & inspection. Complete hinged section opens hydraulically to allow blow bar removal & replacement, apron & liner replacement or major maintenance

Rotor: Cast steel & fitted with 4 reversible & replaceable blow bars

Bearings: Double row self aligning spherical roller bearing fitted each end of rotor

Aprons: Steel aprons with replaceable abrasion resistant wear plate on tip of bottom apron

Drive: Direct through wedge belts with tensioning system on the power unit


Lubrication: Rotor bearings are greased & fitted with inner & outer labyrinth seals

Blow bars: Standard blow bar is martensitic steel, options are available in martensitic ceramic, medium chrome, medium chrome ceramic, high chrome, high chrome ceramic & toughened chrome

APPLICATIONS

This plant is designed for both demolition & quarrying applications. When fitted with martensitic or ceramic blow bars the crusher will tolerate small quantities of steel reinforcing bar in the feed. However, the machine is not designed to accept large pieces (maximum 20mm diameter, 500mm long) of steel or other uncrushable objects, & the feed material should be assessed / inspected for suitability prior to crushing. It is vitally important that large pieces of steel or similar un-crushable objects are not allowed to enter the crushing chamber as severe damage & injury may occur.

When high chrome bars are fitted, all steel should be removed from the feed material & the machine should only be used on quarry applications, or clean materials such as asphalt.





TRAKPACTOR 480


- OVERVIEW
  - FEATURES & BENEFITS
- CRUSHER
  - CRUSHER SPECIFICATION
  - CRUSHER FEATURES
- HOPPER
- VIBRATING GRIZZLY FEEDER
- PRODUCT CONVEYOR
- POWER UNIT & HYDRAULICS
- TRACKS
- PLANT CONTROLS & OTHER
- OPTIONS
  - OPTIONS 1
- POWERSCREEN® PULSE
- DIMENSIONS

HOPPER

Hydraulic folding hopper with wedge-lock system

Loading length:	4.81m (15' 10'')
Hopper width:	2.6m (8' 6'')
Hopper capacity:	7.2m³ (9.4 cu. yd.)
Hopper capacity (extensions):	9.4m³ (12.3 cu. yd.)
Feed in height:	4.25m (13' 11'')
Hopper width (extensions):	3.15m (10' 4'')
Feed in height (extensions rear):	4.25m (13' 11'')
Feed in height (extensions side):	4.53m (14' 10'')
Hopper body:	12mm thick abrasion resistant steel plate

Hydraulic locking as standard.





TRAKPACTOR 480

- OVERVIEW
  - FEATURES & BENEFITS
- CRUSHER
  - CRUSHER SPECIFICATION
  - CRUSHER FEATURES
- HOPPER
- VIBRATING GRIZZLY FEEDER
- PRODUCT CONVEYOR
- POWER UNIT & HYDRAULICS
- TRACKS
- PLANT CONTROLS & OTHER
- OPTIONS
  - OPTIONS 1
- POWERSCREEN® PULSE
- DIMENSIONS

VIBRATING GRIZZLY FEEDER

Type: Spring mounted vibrating

Vibrating unit: Twin heavy duty cast eccentric shafts running in spherical roller bearings. Gears coupled at non-drive end

Length: 4.41m (14' 6")

Width: 1.16m (3' 10")

Pan: 12mm (0.5") thick abrasion resistant steel base plate liners


Drive: Flange mounted hydraulic motor

Grizzly: 2m (6' 7") long double section of welded tapered finger bars at 34mm (1.33") as standard or 38mm (1.5"), 50mm (2"), 60mm (2.4"), 63mm (2.5") & 75mm (3") optional nominal spacing fabricated in 20mm thick abrasion resistant steel

Mesh: Blanking mat standard, underscreen mesh available in 10mm (0.4''), 20mm (0.8''), 30mm (1.2''), 40mm (1.6'') & 50mm (2'')

Punch plate: Available in 30mm (1.2''), 38mm (1.5''), 50mm (2''), 60mm (2.4''), 63mm (2.5'') & 75mm (3'')

Chute: Plant is fitted with a bypass chute, with an internal two way flap door to control direction of fines, either forward onto the product belt or down onto the optional bypass conveyor





TRAKPACTOR 480

- OVERVIEW
  - FEATURES & BENEFITS
- CRUSHER
  - CRUSHER SPECIFICATION
  - CRUSHER FEATURES
- HOPPER
- VIBRATING GRIZZLY FEEDER
- PRODUCT CONVEYOR
- POWER UNIT & HYDRAULICS
- TRACKS
- PLANT CONTROLS & OTHER
- OPTIONS
  - OPTIONS 1
- POWERSCREEN® PULSE
- DIMENSIONS

PRODUCT CONVEYOR

Conveyor type:	Fully removable modular unit. Shallow troughed with winged rollers & fully tunnelled with minimal snag areas
Belt type:	Toughflex EP500/3 8+2 with steel wire breaker ply
Belt width:	1100mm (43")
Discharge height:	3.78m (12' 6") when fully raised
Stockpile volume:	99m³ (130 cu. yd.)
Feedboot:	Fabricated steel with abrasion resistant steel liners
Impact area:	Heavy duty under crusher impact bars
Skirting:	Fully skirted in rubber up to magnet discharge area
Drive:	Hydraulic motor direct to head drum
Lubrication:	Centralised grease points for lubrication of shaft bearings
Belt covers:	Optional aluminium removable dust covers
Belt adjustment:	Belt tensioning is by use of screw adjustment at the head drum
Speed wheel:	Designed to stop plant feed if the discharge conveyor slows or stops

DUST SUPPRESSION SYSTEM

Spray bars with atomiser nozzles mounted over product conveyor and piped to an inlet manifold for customer water supply or optional pump.

Type:	Clean water multi atomising nozzles
Inlet:	Single point on chassis
Inlet pressure:	3 bar (44psi)
Water supply:	24 L/min (6.3G/min) minimum
Frost protection:	Via system main valves
Pump:	Optional





TRAKPACTOR 480

- OVERVIEW
  - FEATURES & BENEFITS
- CRUSHER
  - CRUSHER SPECIFICATION
  - CRUSHER FEATURES
- HOPPER
- VIBRATING GRIZZLY FEEDER
- PRODUCT CONVEYOR
- POWER UNIT & HYDRAULICS
- TRACKS
- PLANT CONTROLS & OTHER
- OPTIONS
  - OPTIONS 1
- POWERSCREEN® PULSE
- DIMENSIONS

POWER UNIT & HYDRAULICS

Tier 2 Equivalent:	Scania DC9 294 kW (400hp)
Operating conditions:	Ambient temp.+30°C to –5°C (86ºF to 23ºF) at altitudes up to 2000m (6562ft) above sea level - For applications outside this range please consult with Powerscreen as the plant performance / reliability may be affected.
Operating rpm range:	1500 - 1900rpm
Emission control technique:	Not applicable
Plant drive:	High quality pumps driven via engine PTO's
Clutch type:	Desch Revox 14'' wet clutch

Tier 4F:	Scania DC9 294 kW (400hp)
Operating conditions:	Ambient temp.+30°C to –5°C (86ºF to 23ºF) at altitudes up to 2000m (6562ft) above sea level - For applications outside this range please consult with Powerscreen as the plant performance / reliability may be affected
Operating rpm range:	1500 - 1900rpm
Emission control technique:	Selective Catalytic Reduction (SCR)
Plant drive:	High quality pumps driven via engine PTO
Clutch type:	Desch Revox 14'' wet clutch

Stage V:	Scania DC9 294 kW (400hp)
Operating conditions:	Ambient temp.+30°C to –5°C (86ºF to 23ºF) at altitudes up to 2000m (6562ft) above sea level - For applications outside this range please consult with Powerscreen as the plant performance / reliability may be affected
Operating rpm range:	1500 - 1900rpm
Emission control technique:	Selective Catalytic Reduction (SCR)
Plant drive:	High quality pumps driven via engine PTO
Clutch type:	Desch Revox 14'' wet clutch

Fuel tank capacity:	769 L (203 US Gal)
Hydraulic tank capacity:	636 L (168 US Gal)
Reductant tank capacity:	60 L (16 US Gal)

Crusher drive:	Direct drive via wedge belts Crushing performance can be tuned by changing engine speed via the PLC .
Drive tensioning:	VEE belt tensioner system
Tip speed range::	4 high blow bars: 30 - 35m/s 2 high blow bars: 35 - 40m/s



TRAKPACTOR 480

- OVERVIEW
  - FEATURES & BENEFITS
- CRUSHER
  - CRUSHER SPECIFICATION
  - CRUSHER FEATURES
- HOPPER
- VIBRATING GRIZZLY FEEDER
- PRODUCT CONVEYOR
- POWER UNIT & HYDRAULICS
- TRACKS
- PLANT CONTROLS & OTHER
- OPTIONS
  - OPTIONS 1
- POWERSCREEN® PULSE
- DIMENSIONS

TRACKS

TRACKS

Type:	Heavy duty tracks, bolted to chassis on pads & pins
Sprocket centres:	3.72m (12’ 2”)
Track width:	500mm (1’ 8”)
Gradeability:	30° maximum
High speed:	1kph (0.63 mph)
Drive:	Two integral hydraulic motors
Tensioning:	Hydraulic adjuster, grease tensioned





TRAKPACTOR 480

- OVERVIEW
  - FEATURES & BENEFITS
- CRUSHER
  - CRUSHER SPECIFICATION
  - CRUSHER FEATURES
- HOPPER
- VIBRATING GRIZZLY FEEDER
- PRODUCT CONVEYOR
- POWER UNIT & HYDRAULICS
- TRACKS
- PLANT CONTROLS & OTHER
- OPTIONS
  - OPTIONS 1
- POWERSCREEN® PULSE
- DIMENSIONS

PLANT CONTROLS & OTHER

GUARDS

Wire mesh, sheet metal or GRP guards are provided for all drives, flywheels, pulleys & couplings.

The guards provided are designed & manufactured to CE & ANSI standards.

PLATFORMS

Platforms are provided for maintenance on both sides of the feeder & impactor, these are fitted with double row handrails & access ladders.

CHASSIS

Heavy duty I-section of welded construction provides maximum strength & accessibility

PLANT CONTROLS

Full PLC control system

Full colour backlit screen

Complete pictorial user controls

Multi-function backlit menu buttons

Full system diagnostics


Sequential auto start up

Main controls

- Engine/crusher speed
- Feeder (start/stop/speed)
- Product conveyor (start/stop)
- Product conveyor raise/lower
- Side conveyor
- Crusher control/screen setup

UMBILICAL CONTROL

An umbilical control unit is supplied with the plant. This is used to control the tracking function & is also fitted with a stop button for the plant.





TRAKPACTOR 480

- OVERVIEW
  - FEATURES & BENEFITS
- CRUSHER
  - CRUSHER SPECIFICATION
  - CRUSHER FEATURES
- HOPPER
- VIBRATING GRIZZLY FEEDER
- PRODUCT CONVEYOR
- POWER UNIT & HYDRAULICS
- TRACKS
- PLANT CONTROLS & OTHER
- OPTIONS
  - OPTIONS 1
- POWERSCREEN® PULSE
- DIMENSIONS

OPTIONS

BYPASS CONVEYOR

Conveyor type: Troughed EP400/3 4+2 covers hydraulically folding
Belt width: 650mm (26'')
Discharge height: 2.59m (8' 6")
Stockpile volume: 32m³ (42 cu. yd.)
Drive: Direct hydraulic motor
Lubrication: Centralised grease points for lubrication of shaft bearings
Position: RHS or LHS

SINGLE POLE & TWIN POLE MAGNETS

Magnet type: Suspended self cleaning over band with endless belt
Magnet block: 836 x 530mm (33" x 21")
Drive: Direct drive hydraulic motor
Control: Pre-set variable speed
Discharge: Via stainless steel shedder plate
Hydraulic raise / lower
RHS discharge only

BLOW BARS

Standard blow bars supplied with plant are 2 high & 2 half martensitic steel. 2 further options are available:

High chrome: Suitable for medium to hard rock applications where no steel is present in the feed material. Good wear characteristics
Ceramic: Suitable for applications with limited steel in feed. Improved wear characteristics over standard martensitic blow bars
4 full blow bars: Available in all options

HOT/COLD CLIMATE OILS

Cold climate oils - (recommended for ambient temperatures between -20 to +30ºC) - Hydraulic & lubrication oils only. Other component modifications may be required for low temperature operations. Please contact the Powerscreen sales & applications department with any queries.

Hot climate oils - (recommended for ambient temperatures between +15 to +50ºC)

HOPPER EXTENSIONS

Hopper width: 3.15m (10' 4'')
Hopper capacity: 9.4m³ (12.3 cu. yd.)
Body: 12mm thick abrasion resistant steel plate





TRAKPACTOR 480

- OVERVIEW
  - FEATURES & BENEFITS
- CRUSHER
  - CRUSHER SPECIFICATION
  - CRUSHER FEATURES
- HOPPER
- VIBRATING GRIZZLY FEEDER
- PRODUCT CONVEYOR
- POWER UNIT & HYDRAULICS
- TRACKS
- PLANT CONTROLS & OTHER
- OPTIONS
  - OPTIONS 1
- POWERSCREEN® PULSE
- DIMENSIONS

OPTIONS 1

OTHER OPTIONS

- Grizzly decks 50mm, 63mm & 75mm
- Punch plates cartridges 38mm, 50mm, 63mm & 75mm
- High chrome blow bars
- Ceramic blow bars
- 4 full size blow bars in lieu of 2 full 2 half blow bars
- Left and right hand bypass conveyor
- Single pole or twin pole over-band magnets (hydraulic raise/ lower)
- Plant lighting
- Mechanical belt weigher
- Electric water pump for dust suppression
- Hot/cold climate oils
- Hopper extensions
- Dust covers





TRAKPACTOR 480

- OVERVIEW
  - FEATURES & BENEFITS
- CRUSHER
  - CRUSHER SPECIFICATION
  - CRUSHER FEATURES
- HOPPER
- VIBRATING GRIZZLY FEEDER
- PRODUCT CONVEYOR
- POWER UNIT & HYDRAULICS
- TRACKS
- PLANT CONTROLS & OTHER
- OPTIONS
  - OPTIONS 1
- POWERSCREEN® PULSE
- DIMENSIONS

POWERSCREEN PULSE

RECORD, DISPLAY AND ANALYSE DATA:

HIGH EFFICIENCY THROUGH PRECISE INFORMATION

Available online anywhere and at any time: comprehensive information on the GPS location, start and stop times, fuel consumption, tonnages, cone settings, wear ratings, operating hours, maintenance status, and much more.



AVAILABLE ANYWHERE AND AT ANY TIME

DASHBOARD DISPLAY

FLEET OVERVIEW

WEEKLY REPORT DIRECT TO YOUR INBOX

GPS: MACHINE TRACKING

REPORTING
UTILISATION, PERFORMANCE & PART SPECIFIC







TRAKPACTOR 480

- OVERVIEW
  - FEATURES & BENEFITS
- CRUSHER
  - CRUSHER SPECIFICATION
  - CRUSHER FEATURES
- HOPPER
- VIBRATING GRIZZLY FEEDER
- PRODUCT CONVEYOR
- POWER UNIT & HYDRAULICS
- TRACKS
- PLANT CONTROLS & OTHER
- OPTIONS
  - OPTIONS 1
- POWERSCREEN® PULSE
- DIMENSIONS

DIMENSIONS

Figure 1: Trakpactor 480
Working Position





MORE DIMENSIONS OVERLEAF




TRAKPACTOR 480

- OVERVIEW
  - FEATURES & BENEFITS
- CRUSHER
  - CRUSHER SPECIFICATION
  - CRUSHER FEATURES
- HOPPER
- VIBRATING GRIZZLY FEEDER
- PRODUCT CONVEYOR
- POWER UNIT & HYDRAULICS
- TRACKS
- PLANT CONTROLS & OTHER
- OPTIONS
  - OPTIONS 1
- POWERSCREEN® PULSE
- DIMENSIONS

DIMENSIONS

Figure 2: Trakpactor 480
Transport Position



Powerscreen equipment complies with CE requirements.

Please consult Powerscreen if you have any other specific requirements in respect of guarding, noise or vibration levels, dust emissions, or any other factors relevant to health and safety measures or environmental protection needs. On receipt of specific requests, we will endeavour to ascertain the need for additional equipment and, if appropriate, quote extra to contract prices.

All reasonable steps have been taken to ensure the accuracy of this publication, however due to a policy of continual product development we reserve the right to change specifications without notice.

It is the importers' responsibility to check that all equipment supplied complies with local legislation regulatory requirements.

Plant performance figures given in this brochure are for illustration purposes only and will vary depending upon various factors, including feed material gradings and characteristics. Information relating to capacity or performance contained within this publication is not intended to be, nor will be, legally binding.

GET IN TOUCH

Dungannon
200 Coalisland Road, Dungannon,
Co Tyrone, BT71 4DR, Northern Ireland
Tel: +44 (0) 28 87 718 500
Fax: +44 (0) 28 87 747 231

Louisville
11001 Electron Drive,
Louisville, Kentucky, 40299 USA
Tel: +1 502 736 5200
Fax: +1 502 736 5202

www.powerscreen.com